



Built-in driver

Durable and reliable power source, all in one design.

Manual Dimmer
0-10V Control Port
Input 220-240V AC




PC Cover
protect the fixture chips from the influence of growing environment


Specifications

Input Power	720W
Light Bar Qty	6 Bar
Efficacy	2.7 $\mu\text{mol}/\text{J}$
PPF	1944 $\mu\text{mol}/\text{s}$
Input Voltage	220-240V AC
Voltage	3.0-3.3A
Chip	Branded LEDs
Mounting Height	$\geq 12"$ (30cm) Above Canopy
Lifetime	50,000hrs
Power Factor	$>90\%$
Colour Rendering Index	90ra
Ambient Temperature	-25~40°C
Control	0-10V Control
Certifications	ETL , CE , UKCA
Package Size	1150x105x570mm
LED Fixture	1110x1065x38mm

Spectrum



PAR Distribution





Built-in driver

Durable and reliable power source, all in one design.



Manual Dimmer
0-10V Control Port
Input 220-240V AC




PC Cover
protect the fixture chips from the influence of growing environment


Specifications

Input Power	720W
Light Bar Qty	6 Bar
Efficacy	2.9 $\mu\text{mol}/\text{J}$
PPF	2088 $\mu\text{mol}/\text{s}$
Input Voltage	220-240V AC
Voltage	3.0-3.3A
Chip	Branded LEDs
Mounting Height	$\geq 12"$ (30cm) Above Canopy
Lifetime	50,000hrs
Power Factor	$>90\%$
Colour Rendering Index	90ra
Ambient Temperature	-25~40°C
Control	0-10V Control
Certifications	ETL , CE , UKCA
Package Size	1150x105x570mm
LED Fixture	1110x1065x38mm

Spectrum




PAR Distribution



**Built-in driver**

Durable and reliable power source, all in one design.




Manual Dimmer
0-10V Control Port
Input 220-240V AC

**PC Cover**

protect the fixture chips from the influence of growing environment

Specifications

Input Power	720W
Light Bar Qty	6 Bar
Efficacy	3.1 $\mu\text{mol}/\text{J}$
PPF	2232 $\mu\text{mol}/\text{s}$
Input Voltage	220-240V AC
Voltage	3.0-3.3A
Chip	Branded LEDs
Mounting Height	$\geq 12"$ (30cm) Above Canopy
Lifetime	50,000hrs
Power Factor	$>90\%$
Colour Rendering Index	90ra
Ambient Temperature	$-25\sim 40^{\circ}\text{C}$
Control	0-10V Control
Certifications	ETL , CE , UKCA
Package Size	1150x105x570mm
LED Fixture	1110x1065x38mm

Spectrum**PAR Distribution**

		Height of 12"/30cm						Height of 24"/60cm					
		120CM (4FT)						120CM (4FT)					
120CM (4FT)		235	406	465	468	441	268	261	374	429	438	392	283
		481	899	1024	1036	1034	611	389	570	657	670	597	429
		631	1166	1290	1307	1288	756	482	706	816	828	738	519
		711	1277	1333	1302	1260	726	504	727	828	833	738	515
		612	1091	1091	1057	1015	582	432	606	686	682	605	425
		272	458	482	476	447	266	287	395	448	451	394	283
		Height of 36"/90cm						Height of 48"/120cm					
		120CM (4FT)						120CM (4FT)					
120CM (4FT)		243	310	347	352	319	254	205	243	264	266	246	210
		311	404	455	460	416	329	240	289	317	318	294	248
		358	469	530	536	484	376	263	320	351	353	325	271
		364	470	534	538	483	375	265	319	351	353	326	271
		327	413	464	464	418	328	244	290	318	319	294	246
		250	315	351	354	316	251	202	240	262	265	242	205